

AAD-OUT4-F32

4-Channel Analog & Digital Audio Output Card



AAD-OUT4-F32 is a four-channel analog and digital output card for the VS-3232 Series Modular Multi-Format Digital Matrix Switchers. The AAD-OUT4-F32 outputs four analog and digital signals from the chassis

FEATURES

Balanced Analog Audio over Terminal Block Connector S/PDIF Digital Audio over RCA Connector



TECHNICAL SPECIFICATIONS

PORTS: 4 S/PDIF (digital audio) on RCA connectors, 4 balanced audio stereo (analog

audio) on 5-pin terminal blocks

TOTAL BANDWIDTH: Analog (-3db): >100kHz, Digital: 32kHz - 192kHz sample frequency

POWER 10W

CONSUMPTION:

OPERATING TEMPERATURE:

0° to +40°C (32° to 104°F)

STORAGE -40° to $+70^{\circ}$ C (-40° to 158° F)

CE

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

SAFETY

REGULATORY COMPLIANCE:

ENVIRONMENTAL

REGULATORY COMPLIANCE:

Complies with appropriate requirements of RoHs and WEEE

Product Dimensions 22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H

Product Weight 0.3kg (0.7lbs) approx

Shipping Dimensions $25.00cm \times 22.50cm \times 5.50cm (9.84" \times 8.86" \times 2.17") W, D, H$

Shipping Weight 0.5kg (1.1lbs) approx