



KRAMER

C-GF/5BM

15-pin HD to 5 BNC Breakout Cable

| VGA/UXGA - 15-pin HD



Kramer's C-GF/5BM graphics video breakout cable is constructed of 5 mini coax cables with a molded 15-pin HD (M or F) on one end and 5 BNC (M or F) on the other. It converts between the two most common cabling formats used for routing computer graphic video signals, 15-pin HD, and 5 BNC

FEATURES

Quality Construction - Constructed using Kramer BC-5X high resolution mini coax cable, terminated with molded 15-pin HD connector on one end and 75Ω BNC connectors on the other

Easy Installation - Models 6ft or longer have an 18in (460mm) long spread at the 5 BNC end to fit large routers/switchers such as the Sierra Pro 32 series

Cable Specs - See Kramer BC-5X for detailed cable specs

Varied Selection of Lengths - 0.5 to 100ft (0.2 to 30.5m)



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|---------------------------|--|
| Attenuation (dB/100 ft.): | -0.6 dB @ 1MHz. -1.4 dB @ 5 MHz. -2.1 dB @ 10 MHz. -4.7 dB @ 50MHz. -6.8 dB @ 100MHz. -9.2 dB @ 180MHz. -14.2 dB @ 400MHz. -20.1 dB @ 750MHz. -23.8 dB @ 1000MHz |
| Coax Center Conductor: | 28 AWG 7/36 tinned copper |
| Dielectric: | Foam polyethylene 0.063 inches, 1.6mm |
| Shield: | 90% braid 38 AWG tinned copper |
| Coax Jacket Colors: | Red, green, blue, yellow, black |
| Outer Jacket: | PVC |
| Outer Jacket Color: | Dark Gray w/white lettering |
| Center Conductor: | 0.015 inches, 0.38mm |
| Individual Coax: | 0.108 inches, 2.75mm |
| Outside Diameter: | 0.362 inches, 9.2mm |
| Impedance: | 75Ω |
| DC Resistance: | 72.2Ω per 1000ft, 237Ω per km |
| Capacitance: | 18.3pF per foot, 60pF per meter |
| Velocity of Propagation: | 78% |
| Temperature: | 68° to 167° fahrenheit, - 20° to 75° celsius |
| UL: | CL2 |
| CSA: | C(UL) CL2 |



KRAMER

CONFIGURATIONS

| | |
|-------------|--|
| C-GF/5BM-1 | Molded 15-pin HD (F) to 5 BNC (M) Breakout Cable |
| C-GF/5BM-3 | Molded 15-pin HD (F) to 5 BNC (M) Breakout Cable |
| C-GF/5BM-6 | Molded 15-pin HD (F) to 5 BNC (M) Breakout Cable |
| C-GF/5BM-10 | Molded 15-pin HD (F) to 5 BNC (M) Breakout Cable |
| C-GF/5BM-15 | Molded 15-pin HD (F) to 5 BNC (M) Breakout Cable |
| C-GF/5BM-25 | Molded 15-pin HD (F) to 5 BNC (M) Breakout Cable |