



# KRAMER

## C-GM/GF

15-pin HD to 15-pin HD Cables

| VGA/UXGA - 15-pin HD



Kramer's C-GM/GF computer graphics video cable is a high-performance cable with molded 15-pin HD connectors on both ends. It is used for connecting computer graphics video signals between computers or video scalars and plasma, LCD or other popular display technologies

### FEATURES

**Quality Construction** - High-resolution 26 gauge mini coax for video

**Easy Installation** - Pre-terminated with molded 15-pin HD connectors, gold plated pins and thumbscrews for easy connection

**Varied Selection of Lengths** - Available in versions of 3 to 100ft (0.9 to 30.5m)

**Cable Specs** - See Kramer BC-3X2T7S for detailed cable specs



# KRAMER

## TECHNICAL SPECIFICATIONS

---

Attenuation (dB/100 ft.):	-0.5dB @1MHz.-1.3dB @5MHz.-1.9dB @10MHz.-4.0dB @50MHz.-5.7dB @100MHz.-8.0dB @180MHz.-14.0dB @400MHz
Conductor:	26 AWG 7/34 tinned copper 26 AWG 7/34 tinned copper
Dielectric:	Foam polyethylene with red, green, blue color coding 0.076in (1.95mm)
Shield:	(A) 90% spiral 38 AWG tinned copper.(B) aluminum-foil/Mylar 25% overlap rate (A) 85% braid 36 AWG tinned copper.(B) Mylar 25% overlap rate (A) 85% braid 36 AWG tinned copper.(B) aluminum-foil/Mylar 25% overlap rate
Inner Jacket:	PVC
Jacket Colors:	Black White, white/black, red, red/black Red, orange, brown, yellow, black, red/black
Center Conductor:	0.019in (0.48mm)
Individual Coax:	0.102in (2.6mm)
Impedance:	75Ω
DC resistance:	45Ω/1000ft (148Ω/km)
Capacitance:	17.3pF/ft (57pF/m)
Temperature:	68° to 167°F (-20° to 75°C)
Jacket:	HD polyethylene HD-polyethylene
Diameter:	0.34in (0.88mm) 0.34in (0.88mm)
Conductors:	26 AWG 7/34 tinned copper
Outer Jacket:	PVC
Outer Jacket Color:	Dark gray w/white lettering
Outer Diameter:	0.393in (10.0mm)
UL:	CL2
CSA:	C(UL) CL2



# KRAMER

## CONFIGURATIONS

C-GM/GF-3	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-6	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-10	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-15	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-25	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-35	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-50	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-75	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-100	Molded 15-pin HD (M) to 15-pin HD (F) Cable