



ClareOne Auxiliary Touchpanel CLR-C1-ATP



The ClareOne Auxiliary Touchpanel acts as a secondary control interface for the ClareOne Panel, allowing end users to arm, disarm, monitor, and interact with their security and smart devices. The Touchpanel offers a unique, standalone security interface with additional controls for smart home features. Installation is easy using the supplied wall mount bracket, or the keypad can be placed on a countertop.

Performance Highlights:

- Proximity sensor turns on screen automatically
- · Automatic screen dimming and timeout
- · Connects over Wi-Fi, requiring only a power supply
- Complete control of security and smart home features like locks, lights, thermostat, music, and more
- View live stream from installed ClareVision Plus cameras
- Control many devices at once by running scenes
- Countertop placement or wall mountable
- Dynamic zone status displays opened doors/windows at the top of the zone list
- ClareHome Touchpanel Power Extension Kit can be used for projects that require pre-wire over long distances

Specifications	
Touchscreen	
Screen size	7in (18cm)
Screen resolution	1024x600
Screen type	Capacitive Touch
User Interface	
Proximity sensor	5ft auto-wake motion detection
Power button	Turns on/off device
Volume buttons	Audio volume control +/-
Camera	0.3MP front-facing
Radio/Network	
Wi-Fi	Wi-Fi 802.11 a/b/g/n 2.4 GHz
Micro USB	Future expansion
Bluetooth	Built-in for future use
Power/Battery	
Power input	5WDC
Power connection type	2.5mm barrel connector
Power consumption	2.5W typical, 7.5W max
Battery type	Lithium polymer, 2200mAh
Battery duration	2-3 Hours
,	Z=3 1 IOUIS
Changeable battery	No No
Changeable battery	
Changeable battery Mechanical	No
Changeable battery Mechanical Operating temperature	No 32° to 95° F (0° to 35° C)
Changeable battery Mechanical Operating temperature Storage temperature	No 32° to 95° F (0° to 35° C) 32° to 113° F (0° to 45° C)
Changeable battery Mechanical Operating temperature Storage temperature Operating humidity	No 32° to 95° F (0° to 35° C) 32° to 113° F (0° to 45° C) 5% - 95%
Changeable battery Mechanical Operating temperature Storage temperature Operating humidity Mounting	No 32° to 95° F (0° to 35° C) 32° to 113° F (0° to 45° C) 5% - 95% Includes wall and two-position tabletop stand

Accessories	
CLR-CS-CHT-EXT-10	ClareHome Touchpanel Power Extension Kit

Important Note:

This product is compatible with Legacy Clare Security Systems and the ClareOne System

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.