

The Episode IP 70V amplifier is the perfect combination of brains and brawn. This powerful amp provides premier sound for you and powerful remote management features for your integrator to make your system work smarter.



ESA-70V2CH-500W

## **Easy Configuration**

We've equipped this amp with sophisticated system-management capabilities, which allows your integrator to remotely update firmware, power-cycle the unit, check the status of your device, and more – so you can focus on your business.

## Simple System Control

If your space is equipped with a control system, you can easily power your amp, control volume, and select sources with the push of a button.

## **Safe Operation**

This amp comes equipped with high surge level protection components, and was battle tested in the harshest environments to ensure your system stays up and running.

| Episode IP 70V Amplifier |                           |                           |                           |
|--------------------------|---------------------------|---------------------------|---------------------------|
|                          | ESA-70V2CH-150W           | ESA-70V2CH-300W           | ESA-70V2CH-500W           |
| Power                    | 150W @ 70V x 2CH          | 300W @ 70V x 2CH          | 500W @ 70V x 2CH          |
| Network                  | Ethernet                  | Ethernet                  | Ethernet                  |
| Control                  | IP, IR, RS-232            | IP, IR, RS-232            | IP, IR, RS-232            |
| Local Volume Contol      | Rear Dial (1 Per Channel) | Rear Dial (1 Per Channel) | Rear Dial (1 Per Channel) |
| Power Consumption        | 400W                      | 800W                      | 1200W                     |
| Balanced Input           | 2                         | 2                         | 2                         |
| Unbalanced Input         | 2                         | 2                         | 2                         |
| 12V Trigger              | Yes                       | Yes                       | Yes                       |
| Signal to Noise Ratio    | 95dB                      | 95dB                      | 95dB                      |
| Frequency Response       | 50 Hz - 20,000 Hz         | 50 Hz - 20,000 Hz         | 50 Hz - 20,000 Hz         |
| Weight                   | 7.8 lb                    | 13.56 lb                  | 18 lb                     |
| Height                   | 1U                        | 1U                        | 2U                        |
| Depth                    | 14"                       | 14"                       | 15"                       |

