



## PURPOSE AV - 4MP, EXIR BULLET, OUTDOOR, 2.8MM

## SKU: HNC344-XBSL-2.8

## **FEATURES**

- » 4 MP (2688 x 1520) resolution
- » Full HD 4 MP real-time video
- » Smart Sense
- » IP67 Rating
- » PoE
- » Strobe Light With Built In Speaker
- » H.265
- » Comparable to DS-2CD2T46G1-4I/SL

## **SPECIFICATIONS:**

Туре	Exterior
Image Sensor	1/2.7 Inch Progressive Scan CMOS
Lens	2.8 mm at F1.6
Minimum Illumination	0.012 lux at F1.6 (AGC On), 0 lux with IR
Effective Pixels (H x V)	2688 x 1520
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Alarm Trigger	Tampering Alarm, Network Disconnected, IP Address Conflict, Illegal Login, HDD Full, HDD Error
Frame Rate	30 fps (2688 x 1520)
Shutter Speed	1/3 - 1/100000 sec
Day/Night	ICR
Speco DNR	3D DNR
Wide Dynamic Range	True WDR, 120 dB
Audio	0/1, Built-In Speaker
Focus Setting	Auto
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
Functions	User Authentication, Watermark
IR Range	Up to 240 ft
Mounting Type	Electrical Box/Pole/Corner
Angle Adjustment	Pan: 0 - 360 deg, Tilt: 0 - 90 deg, Rotation: 0 - 360 deg
Streams	Triple
On-Board Storage	Micro SD Slot, Up to 128 GB
Communication Interface	(1) RJ-45 10M/100M Ethernet Port
Enclosure Rating	IP66
Image Settings	Saturation, Brightness, Contrast, Sharp- ness Adjustable Through Client Software or Web Browser
System Compatibility	ONVIF (Profile S, Profile G), ISAPI
Power Supply	12 VDC +/-10%, PoE (802.3af, Class 3)
Power Consumption	11 W Maximum
Temperature Rating	-22 to 140 deg F
Relative Humidity	95% or Less (Non-Condensing)











