



HNC344G2-XD-LU-RB



FEATURES

4MP True WDR Smart Color Turret, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- PoE
- Full Color Night View
- H.265

| Specifications | |
|-------------------------|--|
| Model Number | HNC344G2-XDLURB/2.8 |
| Image Sensor | 1/1.8" progressive scan CMOS |
| Min. illumination | 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light |
| Shutter time | 1/3s ~ 1/100,000s |
| Lens | 2.8mm, |
| Angle adjustment | Pan: 0° ~ 360°, tilt 0° ~ 75°, Rotation: 0 ~ 360° |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | True WDR 120dB |
| Day & night | 24/7 Color |
| Video compression | Main stream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEG |
| Triple stream | NO |
| Audio In | Yes (built in mic) |
| Alarm | N/A |
| Max. image resolution | 2688×1520 |
| Frame rate | 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720) |

| Specifications | |
|-------------------------|---|
| Image settings | Saturation, brightness, contrast, sharpness adjustable through client software or web browser |
| BLC | Yes |
| On Board Storage | Micro SD slot, up to 128GB |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos |
| API | ONVIF(Profile S, Profile G), ISAPI |
| General functionalities | User authentication, watermark |
| Communication interface | 1 RJ45 10M / 100M Ethernet interface |
| Operating conditions | -30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing) |
| Power supply | 12 VDC +/- 25%, PoE (802.3af, class 3) |
| Power consumption | Max, 7.6W |
| Ratings | IP66 |
| Visible Light Range | Up to 90ft |
| Dimensions | Ø 138.3 mm × 125.2 mm (Ø 5.4" × 4.9") |
| Weight | 750 g (1.7 lb.) |
| Electrical Box | HTH-280ZJ-DM21 |
| Wall Mount | HTH-273ZJ-140B |
| Pendant | HTH-271ZJ-140 |
| Corner and Pole | C:HTH-276ZJ, P:HTH-275ZJ |