

# HNCA16-FEA



## FEATURES

6MP Fisheye, Exterior, Built-in microphone and speaker

- 1/1.8" progressive scan CMOS
- 6 mega-pixel image sensor
- Up to 3072 x 2048 real-time streaming
- 360° view angle
- Multiple viewing modes
- Multiple ePTZ streams with preset and patrol functions
- Ceiling, Wall or Table mount modes
- Up to 50ft IR range

Specifications	
Model Number	HNCA06-FEA
Image Sensor	1/1.8" progressive scan CMOS
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0.001 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1 s to 1/100,000 s
Lens	1.27mm @F2.6, angle of view: 360°
Lens mount	M12
Day & Night	IR Cut Filter
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Video Bit Rate	32 Kbps - 16 Mbps
Max. Resolution	6MP CMOS, 3072 x 2048
Frame Rate	60Hz: 30fps (3072 × 2048, 2048 × 2048, 1280 × 1280)

<b>Specifications</b>	
Digital Noise Reduction	3D DNR
Wide Dynamic Range	120dB
Image Setting	Saturation, Brightness, Contrast, Hue, Sharpness, AGC, White Balance
Day/night Switch	Auto / Manual / Scheduled / Alarm trigger
Network Storage	NAS
Alarm trigger	Motion detection, dynamic analysis, tamper alarm, network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Security	User Authentication, Watermark, IP address filtering, Anonymous access
Standard	ONVIF, PSIA, CGI
Communication Interface	1 RJ45 10M/100M/1000M Ethernet port 1 RS-485 interface (-S)
On-board storage	Built-in Micro SD/SDXC slot, up to 64 GB
Operating Conditions	-30 °C - 60 °C (-22 °F - 140 °F) Humidity 95% or less (non-condensing)
Power Supply	DC12V±10% / PoE
Power Consumption	Max. 11W
IR range	Max. 50ft
Protection	IK10
Dimensions	164 x 152.8 x 43.8mm (6.46" x 6.02" x 1.72")
Weight	2.25lb
Electrical Box	HTH-280ZJ-DM25, HTH-281ZJ-DM25 (Slanted)
Wall Mount	HTH-273ZJ-DM25
Pendant	HTH-271ZJ-DM25
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ