



## TBUS-201xl

Pop-Up Table Mount Multi-Connection  
Solution

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



Kramer's TBUS-201xl provides an extremely simple, affordable and elegant single-push pop-up multi-connection boardroom solution. By pressing down gently on the lid, the unit opens and closes pneumatically. TBUS-201xl is fast and easy to install and flexible to configure. It customizes to your own needs and is intuitive to operate

### FEATURES

**Pneumatic Lift** - Easy opening & closing by pressing down gently on the cover. When not in use, it lowers flush with the table

**Power Input** - Universal, USA, European and many other worldwide power sockets available

**4 Fixed Inputs** - 15-pin HD, HDMI, 3.5mm & Ethernet

**Elegant and Rugged Rectangular Design** - The sturdy and attractive anodized aluminum enclosure provides maximum connectivity in the smallest possible footprint, and at the same time is cost effective and easy to install

**Installation** - Requires tools and expertise to cut a 133mm x 120mm (5.2" x 4.7") rectangular hole in the surface of the furniture. Maximum table thickness is 7.6cm (3")

**Note** - The power socket module is not included. Purchase the country-specific module separately



# KRAMER

## TECHNICAL SPECIFICATIONS

---

PORTS:	1 HDMI connector, 1 Ethernet RJ-45 connector, 1 15-pin HD connector, 1 3.5mm mini jack
POWER SOCKET ASSEMBLIES:	USA Universal 100–240V AC, 50/60Hz, 5A per outlet; 100–220V AC, 50/60Hz, 5A per outlet; Germany and EU 100–240V AC, 50/60Hz, 5A per outlet; Belgium and France 100–240V AC, 50/60Hz, 5A per outlet; Italy 100–240V AC, 50/60Hz, 5A per outlet; Australia 100–240V AC, 50/60Hz, 5A per outlet; Israel 220V AC, 50/60Hz, 5A per outlet; South Africa 220V AC, 50/60Hz, 5A per outlet; Switzerland 220V AC, 50/60Hz, 5A per outlet; UK 220V AC, 50/60Hz, 5A per outlet; Brazil 220V AC, 50/60Hz, 5A per outlet
OPERATING TEMPERATURE RANGE:	+5° to +45°C (41° to 113°F)
OPERATING HUMIDITY RANGE:	10 to 90% RHL, non-condensing
STORAGE TEMPERATURE RANGE:	-20° to +70°C (-4° to 158°F)
STORAGE HUMIDITY RANGE:	5 to 95% RHL, non-condensing
INCLUDED ACCESSORIES:	Cardboard template
OPTIONS:	Power socket kits, power cord
Product Dimensions	15.20cm x 13.93cm x 17.38cm (5.98" x 5.48" x 6.84" ) W, D, H
Product Weight	0.9kg (2.0lbs) approx
Shipping Dimensions	21.50cm x 19.00cm x 20.70cm (8.46" x 7.48" x 8.15" ) W, D, H
Shipping Weight	1.5kg (3.3lbs) approx





# KRAMER

## CONFIGURATIONS

TBUS-201XL(B) Enclosure - Black Sand Blasted Anodized Aluminum Top

TBUS-201XL(BC) Enclosure - Silver Sand Blasted Anodized Aluminum Top

