





# KRAMER

## TECHNICAL SPECIFICATIONS

INPUT:	1 analog red, green, blue signals: 0.7Vpp/75Ω, H & V sync, TTL level, with loop on 15-pin HD (F) connectors
OUTPUTS:	1 analog red, green (with or without composite sync), blue signals: 0.7 Vpp/75Ω; H & V syncs: TTL level (Hi-Z load) or analog level (75Ω load) on BNC connectors; 1 composite sync: TTL levels (Hi-Z load) or analog level (75Ω load)
VIDEO BANDWIDTH (-3dB):	350MHz
DIFF. GAIN:	0.07%
DIFF. PHASE:	0.03Deg
K-FACTOR:	0.05%
VIDEO S/N RATIO:	71dB
CONTROLS:	Cable EQ, H & V sync shift, G/sync on green switch, Hs/Cs switch, ID bit switch, input termination switch
EQ. CONTROL:	0 to +9.7dB @5MHz
POWER CONSUMPTION:	12V DC, 60mA
INCLUDED ACCESSORIES:	Power supply, mounting bracket
Product Dimensions	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H
Product Weight	0.0kg (0.0lbs) approx
Shipping Dimensions	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50" ) W, D, H
Shipping Weight	0.6kg (1.3lbs) approx

