

Built To Deliver Quality Security – Anywhere

Visualint™ 2MP IP Auto Tracking PTZ Outdoor Camera with Super Starlight + Virtual Technician

This 2MP PTZ camera from Visualint is IP-66 rated for weatherproof outdoor configurations and features 30x optical zoom, smart IR ranging from 180-222m, 16:9 letterbox sensors, glass optics, one-touch auto focus, Super Starlight, and additional features to streamline your installation and deliver unparalleled security to both residential and commercial jobs, broadening the scope of what a surveillance system can do.



Key Features



Embedded Intelligent Analytics



Professional Video Monitoring



PTZ Auto Tracking



Standard Day/Night IR Camera



With Super Starlight



Widescreen & High Definition

Super Starlight Ultra Low-Light Color Sensor

IP66 Outdoor Rating



Product Specs

Technical Specs & Features	VI-7000-PTZ-S-WH
Audio Inputs / Outputs	1-ch / 1-ch
Image Sensor	2MP 1/1.8" CMOS
Maximum Record Resolution	1920 × 1080
Lens	6-180mm, 30x F1.5 ~ F4.3
Est. Horizontal Viewing Angle	61.2°(w) 2.32°(t)
Minimum Illumination	Color: 0.0008 Lux @ (F1.5, AGC ON) , Black & White: 0.0002 Lux @ (F1.5, AGC ON), 0 Lux with IR
IR Range	80 - 200m (262ft - 656ft)
Remote Monitoring Integration	Immix
Recording Trigger	No
Full Screen Monitoring	Yes
Image Snapshot	Yes
Audio Support	1-ch, G.711A/G.711U/ADPCM/AAC
Triggered Action Desc.	Email, HTTP Notification, FTP
SD Card Support	N/A
Network / Ethernet Desc.	10M/100M Ethernet Interface
Supported Network Protocols	TCP, UDP, HTTP, MULTICAST, UPnP, DHCP, PPPoE, DDNS, NFS, FTP, NTP, RTP, RTSP, IPv6, SNMP, SMTP
Power Consumption	AC24V 3A, 18.55W(IR OFF)/ 35.5W(IR ON)
Color	Two-tone White & Black
Dimensions (W x H x D)	14.6" x 8.7" x 8.7"
Weather Rating	IP66
Certifications	CE, FCC
Operating Temperature	-20-140°F, 0~95% RHG
Weight	11 lb

Multiple Video and Snapshot Streams

